

WHAT IS CLAIMED IS:

1. A method of determining an end of a transmitted frame at a receiver on a frame-based communications network comprising:
- 5 providing an end of frame format for the transmitted frame having an end of frame plurality of symbols;
- filtering a received transmitted frame using filter coefficients matched to the end of frame plurality of symbols to
- 10 provide a correlation sequence low-pass filtered signal;
- computing a squared magnitude of the correlation sequence;
- low-pass filtering the squared magnitude of the correlation sequence to provide a low-pass filtered correlation signal;
- 15 delaying the low-pass filtered correlation signal to provide a delayed low-pass filtered correlation signal;
- multiplying the delayed low-pass filtered correlation signal by a fixed predetermined threshold to provide a multiplied correlation signal; and
- 20 comparing the multiplied correlation signal with the low-pass filtered correlation signal to provide a match/no match comparison indicative of the possible end of a transmitted frame.
2. The method of Claim 1, wherein the filtering is linear matched filtering.
- 25 3. The method of Claim 1, wherein the filter coefficients are a time-reversed, complex-conjugated end of frame symbol sequence.
4. The method of Claim 3, wherein the time-reversed complex-conjugated end of frame symbol sequence is a constant-amplitude
- 30 zero-autocorrelation sequence.
5. The method of Claim 3, wherein the time-reversed complex-conjugated end of frame symbol sequence includes complex symbols
- 35 drawn from a Quadrature Phase Shift Keying or 4-Quadrature

Amplitude Modulation constellation.

5 6. The method of Claim 1, wherein the multiplying includes first computing $10 \cdot \log_{10}(\cdot)$, or an approximation of $10 \cdot \log_{10}(\cdot)$, of each operand to provide a plurality of log operands and then adding each of the plurality of log operands.

10 7. The method of Claim 1, wherein the comparing includes performing a comparison a predetermined number of times before an end of a transmitted frame is determined.

15 8. A method of determining an end of a transmitted frame at a receiver on a frame-based communications network comprising:

providing an end of frame format for the transmitted frame having an end of frame plurality of symbols;

20 linear matched filtering a received transmitted frame using filter coefficients matched to the end of frame plurality of symbols to provide a correlation sequence, the filter coefficients being a time-reversed complex-conjugated end of frame symbol sequence including complex symbols drawn from a Quadrature Phase Shift Keying or 4-Quadrature Amplitude Modulation constellation;

25 computing a squared magnitude of the correlation sequence; low-pass filtering the squared magnitude of the correlation sequence to provide a low-pass filtered correlation signal;

delaying the low-pass filtered correlation signal to provide a delayed low-pass filtered correlation signal;

30 multiplying the delayed low-pass filtered correlation signal by a fixed predetermined threshold by first computing $10 \cdot \log_{10}(\cdot)$, or an approximation of $10 \cdot \log_{10}(\cdot)$, of each low-pass filtered correlation signal operand to provide a plurality of low-pass filtered correlation signal log operands and then adding
35 each of the plurality of low-pass filtered correlation signal log

1 42140/RJP/E264

operands to provide a multiplied correlation signal; and

5 comparing the multiplied correlation signal with the low-
pass filtered correlation signal to provide a match/no match
comparison indicative of the possible end of a transmitted frame
and performing a comparison a predetermined number of times
before an end of a transmitted frame is determined.

10

15

20

25

30

35

FOI b0 b7C b7D b7E b7F b7G b7H b7I b7J b7K b7L b7M b7N b7O b7P b7Q b7R b7S b7T b7U b7V b7W b7X b7Y b7Z b8 b9